

Molyspeed Grease No.1,2	SDS No.	2202
SUMICO LUBRICANT CO., LTD.	Revision Date	Mar. 01, 2015

## SAFETY DATA SHEET(SDS)

### 1 PRODUCT AND COMPANY IDENTIFICATION

Product Name : Molyspeed Grease No.1,2  
 Company Name : SUMICO LUBRICANT CO., LTD.  
 Address : Shimbashi Sumitomo Bldg., 11-3, Shimbashi 5-chome Minato-ku, Tokyo 105-0004, Japan  
 Phone Number : +81-3-5401-8513  
 Fax Number : +81-3-5401-0471  
 Mail Address : tech\_sumico@ni.smm.co.jp

### 2 HAZARDS IDENTIFICATION

Hazards Category  
 Classification not possible

Allocation of Label Elements

Pictogram  
 Classification not possible

Signal Word  
 Classification not possible

Hazard Statement  
 Classification not possible

### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients and Contents

Component name	CAS number	wt%
Mineral oil	Trade secret	80~90
Molybdenum disulfide	1317-33-5	1~5
Bentonite	Trade secret	5~10

### 4 FIRST-AID MEASURES

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
 Call a physician if you feel unwell.

Skin

Wash with plenty of soap and water.  
 Call a physician if you feel unwell.

Eye

Immediately flush eyes with plenty of water for at least 15 minutes.  
 Call a physician.

Ingestion

Rinse mouth. Do not induce vomiting.  
 Call a physician.

### 5 FIRE-FIGHTING MEASURES

Extinguishing Media

Dry chemical, carbon dioxide(CO2), and foam

Specific Fire Fighting

Must not use water to extinguish fires.  
 Quickly removed from the surrounding flammable.

Molyspeed Grease No.1,2	SDS No.	2202
SUMICO LUBRICANT CO., LTD.	Revision Date	Mar. 01, 2015

The use of extinguishing agents specified.

Fire fighting is done from the windward.

On small fires use carbon dioxide (CO<sub>2</sub>) or dry chemical.

On large fires use dry chemical or foam.

Sealed containers that are exposed to high temperatures over the water to cool.

Protection for Fire-fighter

Wear full body protective clothing with breathing apparatus.

## 6 ACCIDENTAL RELEASE MEASURES

Personal Precautions

Wear protective equipments in case of operation.

Environmental Precautions

Avoid release to the environment.

Methods for Cleaning Up

Remove potential ignition source in vicinity as soon as possible.

Prepare extinguishing agent.

Prevent leakage by enclosing with nonflammables and collect into empty container by scoop or the like.

Absorbed to non-flammable dry sand, if a large amount of spill to prevent enclosed in embankment.

Spilled material is collected in a container that can be sealed, then remove to safe place.

Deposits, waste treatment is based on the local regulations.

Working from the windward, to evacuate people downwind.

## 7 HANDLING AND STORAGE

Handling

Use in a well ventilated area.

Keep away from heat, spark and flames.

Use spark-proof tools and explosion-proof equipment.

After handling, wash well hands and face and rinse your mouth.

Facilities storing or utilizing this material should be equipped with an eye wash facility and a safety shower.

Leakage, overflow, to prevent scattering, we do not generate steam in vain.

In the handling area and deny unnecessary entry.

Resting place shall not bring contaminated protective equipment such as gloves.

Wear protective equipments when risk of exposure occurs.

To work in an enclosed area that you work with appropriate protective equipment with a local exhaust ventilation sufficient.

Precautions

Do not breathe vapor or mist.

Handling of the outdoors, as much as possible to work from the windward.

Handling Precautions for Safety

Avoid physical damage to containers.

Keep containers securely sealed when not in use.

Storage

Fire prohibited strictly.

Keep away from sources of ignition.

Store in a cool, dry, well-ventilated area away from incompatible substances.

Separate from oxidizing materials.

Store in a tightly closed container.

Safe containers and packaging materials

None in particular.

## 8 EXPOSURE/PERSONAL PROTECTION

Engineering Controls

Handling equipment is used explosion-proof.

Ventilation fans and other electrical service must be non-sparking and have an explosion-proof design.

Molyspeed Grease No.1,2	SDS No.	2202
SUMICO LUBRICANT CO., LTD.	Revision Date	Mar. 01, 2015

That the equipment and shall become hot, and the source of ignition in the vicinity of the location, such as handling not been placed.

Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits.

#### Exposure Limit Values

Chemical name	ACGIH
Mineral oil	TWA 5mg/m <sup>3</sup> (mist)
Molybdenum disulfide	TWA 3mg/m <sup>3</sup>

#### Personal Protective Equipment

##### Respiratory Protection

Wear a gas mask for organic gas as required.

##### Skin Protection

Oil-resistant gloves

##### Eye Protection

Wear chemical worker's goggles.

##### Skin and body protection

Such as long-sleeved work clothes

##### Hygiene measures

Do not eat, drink or smoke during work.

Replacement of the adsorbent, such as the mask is performed each time or use plans.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

Physical State	:	Semi-Solid
Color	:	Dark gray
Odor	:	Oil odor
pH	:	Not available
Boiling Point(°C)	:	Not available
Melting Point(°C)	:	Not available
Flash point(°C)	:	≥200 (Base oil)
Auto-ignition Temperature(°C)	:	Not available
Flammability or Explosive Limits		
Lower	:	Not available
Upper	:	Not available
Vapour Pressure (KPa)	:	Not available
Vapour Density	:	Not available
Relative density(g/cm <sup>3</sup> )	:	0.91
Solubility	:	Insoluble in water
Partition Coefficient: n-octanol/water	:	Not available
Decomposition Temperature(°C)	:	Not available

## 10 STABILITY AND REACTIVITY

### Stability

Stable under normal temperatures and pressures.

### Reactivity

No self-reactive

### Conditions to Avoid

Heat, flames, ignition sources and incompatibles.

### Hazardous Decomposition Products

Carbon monoxide, carbon dioxide and other oxidized substances.

## 11 TOXICOLOGICAL INFORMATION

Molyspeed Grease No.1,2	SDS No.	2202
SUMICO LUBRICANT CO., LTD.	Revision Date	Mar. 01, 2015

Chemical name	Acute toxicity (oral)	Acute toxicity (dermal)	Acute toxicity (inhalation: gas)	Acute toxicity (inhalation: vapour)	Acute toxicity (inhalation: dust, mist)	Skin corrosion / irritation	Serious eye damage / eye irritation
Mineral oil	Classification not possible	Classification not possible	Classification not possible	Classification not possible	Classification not possible	Classification not possible	Classification not possible
Molybdenum disulfide	Classification not possible	Classification not possible	Classification not possible	Classification not possible	Classification not possible	Classification not possible	Classification not possible
Bentonite	Classification not possible	Classification not possible	Classification not possible	Classification not possible	Classification not possible	Classification not possible	Classification not possible

Chemical name	Respiratory/skin sensitizer	Germ cell mutagenicity	Carcinogenicity	Toxic to reproduction	Specific target organs/systemic toxicity following single exposure	Specific target organs/systemic toxicity following repeated exposure	Aspiration hazard
Mineral oil	Respiratory sensitizer: Classification not possible; Skin sensitizer: Classification not possible	Classification not possible	Classification not possible	Classification not possible	Classification not possible	Classification not possible	Classification not possible
Molybdenum disulfide	Respiratory sensitizer: Classification not possible; Skin sensitizer: Classification not possible	Classification not possible	Classification not possible	Classification not possible	Classification not possible	Classification not possible	Classification not possible
Bentonite	Respiratory sensitizer: Classification not possible; Skin sensitizer: Classification not possible	Classification not possible	Classification not possible	Classification not possible	Classification not possible	Classification not possible	Classification not possible

## 12 ECOLOGICAL INFORMATION

Chemical name	Hazardous to the aquatic environment (Acute)	Hazardous to the aquatic environment (Chronic)
Mineral oil	Classification not possible	Classification not possible
Molybdenum disulfide	Classification not possible	Classification not possible
Bentonite	Classification not possible	Classification not possible

## 13 DISPOSAL CONSIDERATIONS

Dispose of contents /container in accordance with local/regional/national/international regulations.

Molyspeed Grease No.1,2	SDS No.	2202
SUMICO LUBRICANT CO., LTD.	Revision Date	Mar. 01, 2015

---

#### 14 TRANSPORT INFORMATION

##### UN Class

Not regulated.

##### UN No.

Not regulated.

##### Packing Group

Not regulated.

---

#### 15 REGULATORY INFORMATION

Follow all regulations in your country.

---

#### 16 OTHER INFORMATION

##### References

JIS Z 7253

GHS data-base (NITE)

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall the company be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if the company has been advised of the possibility of such damages.