

PRODUCT SPECIFICATION FORM

HARRINGTON THREE-PHASE ELECTRIC CHAIN HOISTS

NER/ER THREE-PHASE ELECTRIC CHAIN HOISTS/TROLLEYS

Quantity _____

Capacity _____

Lift _____

Lift Speed _____ C (Common) _____ L (Low)
 _____ S (Standard) _____ H (High)
 _____ Single _____ Dual

Voltage _____ 208-3-60 _____ 230-3-60 _____ 460-3-60 _____ 575-3-60

Control Voltage _____ 110V (standard) _____ 24V

Control _____ Pendant _____ Cylinder Control

Pendant Drop _____ (standard is 4' less than lift)

Power Supply Cord _____
 (standard is 15' thru 5 Ton – hook, push or geared trolley mount)
 (standard is 30' above 5 Ton – hook, push or geared trolley mount)
 (standard is 30' all capacities – motorized trolley mount)

Suspension _____ Hook _____ Lug _____ Trolley (see below)

Options: _____ Canvas Chain Container
 _____ Steel Chain Container
 _____ Plastic Chain Container
 _____ Mechanical Brake (ER standard feature)
 _____ Hoist Mount – Parallel to Beam
 _____ Hoist Mount – Perpendicular to Beam

Trolley Type _____ Push _____ Geared _____ Motorized

Hand Chain Drop _____ (if geared trolley)

Travel Speed _____ L (40 FPM) _____ S (80 FPM) _____
 _____ SD (80/13 FPM) (if motorized trolley)

Beam Type/Size _____

Beam Flange Width _____

Beam Radius _____ (if curved monorail)

Specials: _____

Please contact Harrington's Customer Service Department for further assistance:

Location	Phone Number	Fax Number
Manheim, PA	800-233-3010	717-665-7432
Corona, CA	800-317-7111	951-279-7500

E-mail: customerservice@harringtonhoists.com

Form completed by:

Name _____ Company _____

Phone _____ Fax _____