

MSDS: 45161-1120E51EEN Date Prepared: 2010/07/01 Date Revised: 2015/02/02

Product Name: AUTO

AUTOMATIC D2

# 1. Identification of the substance/mixture and of the company/undertaking

Product Name: Identification of the supplier:	AUTOMATIC D2 JX Nippon Oil & Energy Corporation
Address:	6-3,Otemachi 2-Chome,Chiyoda-ku,Tokyo, 100-8162 Japan
Charge section:	Lubricants Quality Assurance Group (TEL:+81 3-6275-5158)

## 2. Hazards identification

hazard category		Category	
Flammable liquids		No Classification	
Acute toxicity (oral)		No Classification	
	Acute toxicity (dermal)		No Classification
	Specific target organ sy	ystemic toxicity	No Classification
	following single exposur		
	Specific target organ sy		No Classification
	following repeated expos	sure	
	Aspiration hazard		No Classification
	Acute hazards to the aqu		Category 3
	Chronic hazards to the a	aquatic environment	Category 3
LABEL ELEM	ENTS		
	Precautionary	Not applicable	
	Signal word:	Not applicable	
	Hazard Statement:	Harmful to aquation	c life
		Harmful to aquation	e life with long lasting effects
	Precautionary Statements	3:	
	Preventio		il all safety precautions have been read and
		understood.	
		Wear protective gl protection.	loves/protective clothing/eye protection/face
		•	eyes to become exposed to the product. Do not
swallow the produc			
			ghly after handling.
		Do not eat, drink	or smoke when using this product.
	Respons	e IF SWALLOWED: Imme	ediately call a POISON CENTER or
		doctor/physician.	
			se mouth. Do NOT induce vomiting.
			posed to the product: Rinse the eyes with
			water and immediately contact a physician.
			with plenty of soap and water.
		Avoid release to t	
	Storag		be stored in a cool, well-ventilated location
			be exposed to direct sunlight. ave been opened must be tightly sealed.
	Dienosa		ts/container in accordance with
	D13p03a	-	tional/international regulations.
			,



MSDS: 45161-1120E51EEN Date Prepared: 2010/07/01 Date Revised: 2015/02/02

Product Name: AUTOMATIC D2

If there are any doubts about proper methods of handling the product, contact the point of purchase before proceeding with usage.

## 3. Composition/information on ingredients

Substance/Mixture: Ingredients and Concentration	Mixture	
Ingredient Name		Concentrationwt.%
Base Oil(s)		80-90
Additives		<20

### 4. First-aid measures

Inhalation:	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Cover the body with blankets to keep warm and quiet. If you feel unwell, seek medical advice.
Skin Contact:	Immediately flush skin with large amounts of water.
	Wash contaminated clothing before reuse.
	If skin irritation occurs : Get medical advice/attention.
Eye Contact:	Rinse with clean water carefully for several minutes. Remove contact lenses if present and if removal is easy, then continue rinsing. Rinse for 15 minutes at a minimum and seek medical attention.
Ingestion:	Do not induce vomiting. Drink [one glass] [two glasses] of water. Call a physician [or poison control center] immediately.

## 5. Fire-fighting measures

Suitable Extinguishing Media:	Mist of loaded liquid, dry chemicals, carbon dioxide, fire foam, and dry sand are effective.
Extinguishing Media to Avoid:	Use of straight steam of water can cause a risk of spreading fire.
Specific hazards arising from the chemical:	In some cases of fire, may release irritant gases.
	When burnt, may generate carbon monoxide and other toxic gases.
Fire Fighting:	Spray water to the surrounding facilities for cooling.
	Keep unauthorized persons off the site of occurrence of fire and the surroundings.
	Even after extinction, cool containers thoroughly with plenty of water.
Special protective equipment and precautions for fire fighters:	Wear fire/flame resistant/retardant clothing.
	Fight fire from windward direction while wearing protective equipment. If contact with skin is expected, wear impervious protective equipment and gloves.



MSDS: 45161-1120E51EEN Date Prepared: 2010/07/01 Date Revised: 2015/02/02

Product Name: AUTOMATIC D2

Use air-breathing apparatus and protective clothing whenever necessary.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:	Wear protective equipment when working.
	Remove nearby potential ignition sources immediately.
	When mist is generated, use respiratory equipment to prevent inhalation of mist.
	Do not touch or walk through spillage.
	Pay attention to the site of spillage, which is slippery.
Environmental precautions:	Prevent spreading of oil spill with earth and sand, sandbags, or other proper materials and use care not to allow the oil spill to flow to street drains, sewer systems, and rivers. At sea, install oil spill containment booms to prevent spreading of spills and absorb with absorption mat or other proper materials.
Methods and materials for	In case of spillage in small quantity, collect spillage by
containment and cleaning up:	absorbing with earth, sand, sawdust, waste, or other proper materials.
	In case of spillage in large quantity, enclose with embankment to prevent spreading of spillage and collect spillage in empty containers to the extent possible.
Prevention of second accident:	In case of spillage, immediately inform the organizations concerned of the spillage to prevent possible accidents and spreading of spillage.
	Remove nearby potential ignition sources immediately and make fire-extinguishing agents available. Remove spillage completely, and ventilate and clean the site and the surroundings.

## 7. Handling and storage

Handling

Technical Measures:	Keep away from any possible contact with sparks, open flames, and high-temperature materials, and do not allow release of vapor without justification. Use pumps or other proper equipment for taking out from containers. Do not siphon with your mouth using a tube. Do not
	drink.
	When mist is generated, use respiratory equipment to prevent inhalation of mist.
	In case of vapor/mist dispersion, install a closed system, local ventilation system, and/or other proper equipment for the sources of vapor/mist generation.
	Avoid rough handling of containers such as falling, dropping, exposing to shock, and dragging.
Ventilation requirements:	Maintain adequate ventilation when handling indoors.
Precautions:	Wash hands and face thoroughly after handling.
	Be careful with fire.



MSDS: 45161-1120E51EEN Date Prepared: 2010/07/01 Date Revised: 2015/02/02

Pro	oduct Name: AUTOMAT	TIC D2
	Precautions for safe handling:	Avoid falling, dropping, exposing to shock, or dragging of containers. Wear protective gloves when opening containers to eliminate a risk of hand injury.
Storage	Storage Conditions:	Store in a well ventilated, cool, dry, dark place, protecting from direct sunlight and keeping away from any potential ignition sources and high-temperature materials. Store tightly stopped after use to prevent possible contamination with dust and moisture. Preferably store locked up in a proper storage area.
	Safety adequate container materials:	Use spill-proof containers that are free of damage/corrosion.

## 8. Exposure controls/personal protection

Appropriate engineering controls:

In case of mist generation, enclose the source of mist generation, or install a ventilation system. Install eye cleaning and body cleaning equipment near the handling site.

#### Control parameters

Ingredient Name	Japan Society for Occupational	ACGIH	
Ingreatent Name	Occupational Exposure Limits	TLV-STEL	TLV-TWA
Base Oil(s)	None established	None established	None established
	3mg/m3(Mineral Oil		ppm, 5mg/m3(Mineral Oil Mist)

#### Personal Protective Equipment

Respiratory Protection:	Not needed under normal conditions, but wear a gas mask (against organic gases) whenever required.
Hand protection:	In case of prolonged or repeated exposure, wear oil-resistant hand protection.
Eye/face protection: Skin Protection:	In case of exposure to splashes, wear ordinary type goggles. In case of handling over a prolonged period of time or in case of exposure to oil, wear oil-resistant, long-sleeved work clothing.
Hygiene Measures:	Take off contaminated clothing and wash thoroughly before reuse. Wash hands thoroughly after handling.

#### 9. Physical and chemical properties

Product

Physical state:	Liquid
Form:	Liquid
Color:	Red
Odor:	Slight odor



MSDS: 45161-1120E51EEN Date Prepared: 2010/07/01 Date Revised: 2015/02/02

Product Name: AUTOMATIC D2

Pour Point-45(°C) Melting point/freezing point: Initial boiling point - End point No data Initial boiling point and boiling range: Flash point: 196(°C)Cleveland Open Cup  $\text{Estimate200} - 410\,(^{\circ}\text{C})$ Auto-ignition temperature: Upper/lower flammability Explosion Limit (1-7%) or explosive limits: Vapour density: No data. Density(g/cm3):  $0.869(15^{\circ}C)$ water : Insoluble. Solubility: Partition coefficient: No data. n-octanol/water: Decomposition No data. temperature:

#### 10. Stability and reactivity

Chemical stability: Stable when stored or preserved in a dark place at room temperature. Possibility of hazardous reactions: Conditions to avoid: Contact with incompatible hazard substances Prolonged heating, open flames, and ignition sources Incompatible materials: Use care to keep away from any possible contact with halogens, strong acids, alkalis, and acidifying substances. Hazardous decomposition products:

### 11. Toxicological information

Product

Acute toxicity (oral):	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Acute toxicity (dermal):	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Acute toxicity (inhalation):	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Skin corrosion/irritation:	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Serious eye damage/irritation:	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Respiratory sensitization:	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Skin sensitization:	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Mutagenicity:	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Carcinogenicity:	For mixtures, hazard category was identified based on the classification criteria for mixtures.



Product Name:

### SAFETY DATA SHEET

MSDS: 45161-1120E51EEN Date Prepared: 2010/07/01 Date Revised: 2015/02/02

For mixtures, hazard category was identified based on

the classification criteria for mixtures.

AUTOMATIC D2

Reproductive	toxicity:
Reproductive	COALCIUJ.

Target organ effect/Single exposure: Target organ effect/Multi exposure: Respiratory toxic:

#### Ingredient

Base Oil(s) Acute toxicity (oral): Acute toxicity (dermal): Serious eye damage/irritation: Skin sensitization: Mutagenicity: Carcinogenicity: Base Oil(s) LD50:≧ 5000 mg/kg[rat] Practically None [rabbit] None Buehler method [guinea pig] Ames Test:Negative EU:Category 2: R45 need not apply. (NOTE L is Applicable), IARC:3

#### 12. Ecological information

#### Product

110uuct		
Ecotoxicity		
Fish acute	toxicity:	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Algae acute	toxicity:	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Fish chroni	c toxicity:	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Algae chron	ic toxicity:	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Ingredient		
Base Oil(s)		
Ecotoxicity		
Fish acute	toxicity:	96hLC50:> 5000 mg/L[Oncorhynchus mykiss]
Daphnia acu	te toxicity:	48hEC50:> 1000 mg/L[Daphnia magna]

#### 13. Disposal considerations

Disposal Dispose of contents/container in accordance with local/regional/national/international methods: regulations. Every customer/user of the product should dispose of industrial waste on its own responsibility, otherwise it must rely on a company authorized by prefectural governor for treating industrial waste or a local public body involved in the disposal of industrial

waste for proper disposal.

Before disposal of used container, remove contents completely.

### 14. Transport information



MSDS: 45161-1120E51EEN Date Prepared: 2010/07/01 Date Revised: 2015/02/02

Product Name:

AUTOMATIC D2  $\,$ 

IMDG UN classification: Specific security precaution and condition of transportation: Not applicable Transport containers without causing any significant friction or shaking.

## 15. Regulatory information

Korea(KECL) :	All components are listed or exempted.
Australia(AICS) :	All components are listed or exempted.
Canada(DSL) :	All components are listed or exempted.
China(IECSC) :	All components are listed or exempted.
EU(REACH) :	In the case where one or more components are not listed or, even if
	listed, in the case of importing to the country or area concerned, an
	application or notification is required.
New Zealand(NZIoC) :	All components are listed or exempted.
USA(TSCA) :	All components are listed or exempted.
Philippines(PICCS) :	All components are listed or exempted.
Taiwan:	All components are listed or exempted.

### 16. Other information

Disclaimer

We at JX Nippon Oil & Energy Corporation have prepared the copyrighted Safety Data Sheet to provide reference information on the hazardous chemical product of interest for our customers/users to ensure secure and safe handling. We would like every customer/user of the product to refer to the information and understand the necessity of taking appropriate measures for the actual handling conditions on their own responsibilities for optimum practical application of the product of interest. Consequently, the Safety Data Sheet is not intended to guarantee the

safety of the product referenced to herein.